

Skydrol®LD4 Fire Resistant Hydraulic Fluid

Version 1.5 PRD Revision Date: 01/05/2023 SDS Number: 150000093409 Date of last issue: 08/06/2020
SDSUS / Z8 / 0001 Date of first issue: 09/06/2016

SECTION 1. IDENTIFICATION

Product name : Skydrol® LD4 Fire Resistant Hydraulic Fluid

Product code : 34102-00, P3410207, P3410200, P3410206, P3410204, P3410202, P3410205, P3410203, E3410201, P3410208, P3410209

Manufacturer or supplier's details

Company name of supplier : Eastman Chemical Company

Address : 200 South Wilcox Drive
Kingsport TN 37660-5147

Telephone : (423) 229-2000

Emergency telephone : CHEMTREC: +1-800-424-9300, +1-703-527-3887 CCN7321

Recommended use of the chemical and restrictions on use

Recommended use : Hydraulic fluids

Restrictions on use : None known.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Carcinogenicity : Category 2

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H315 Causes skin irritation.
H351 Suspected of causing cancer.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 150000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

and understood.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Components**

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|------------|-----------------------|
| Tributyl phosphate | 126-73-8 | 55 - 65 |
| Dibutylphenylphosphate | 2528-36-1 | 20 - 30 |
| Butyl diphenyl phosphate | 2752-95-6 | 5 - 10 |
| 7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester | 62256-00-2 | < 10 |
| butylated hydroxytoluene | 128-37-0 | 1 |

Eastman is committed to the safety, health and environment of our employees, our customers, and the communities we operate within. As part of this commitment, Eastman's Safety Data Sheets (SDS) are prepared in accordance with all applicable national and local regulations. The compositions of our documents reflect these requirements which include, but are not limited to, requirements under the Globally Harmonized System of Classification and Labeling (GHS). These compositions commonly involve the use of ranges versus specific analytical values. If you require a composition that is more specific, please refer to the Certificate of Analysis, sales specification, or contact your Customer Service Representative.

SECTION 4. FIRST AID MEASURES

| | | |
|-------------------------|---|--|
| If inhaled | : | Move to fresh air. If breathing is difficult, give oxygen. Consult a physician if necessary. |
| In case of skin contact | : | Wash off immediately with plenty of water for at least 15 |

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 150000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

- minutes.
Get medical attention if symptoms occur.
Wash contaminated clothing before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Get medical attention if symptoms occur.
- If swallowed : Call a physician or poison control center immediately.
Do not induce vomiting without medical advice.
Rinse mouth.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Suspected of causing cancer.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
Dry chemical
Foam
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.
- Hazardous combustion products : Carbon monoxide
Carbon dioxide (CO₂)
oxides of phosphorus
- Further information : Use a water spray to cool fully closed containers.
Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Ventilate the area.
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Avoid contact with skin and eyes.
Material can create slippery conditions.
Wear appropriate personal protective equipment.
Local authorities should be advised if significant spillages cannot be contained.
- Environmental precautions : Clear up spills immediately and dispose of waste safely.
Avoid release to the environment.

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 15000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

Collect spillage.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapors or spray mist.
Handle product only in closed system or provide appropriate exhaust ventilation at machinery.
In case of insufficient ventilation, wear suitable respiratory equipment.
Wear appropriate personal protective equipment.
Avoid contact with skin, eyes and clothing.
Wash thoroughly after handling.
Wash contaminated clothing before reuse.
Drain or remove substance from equipment prior to break-in or maintenance.
Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage : Store locked up.
Keep container tightly closed in a dry and well-ventilated place.
Keep in a cool place away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--------------------------|-----------|------------------------------------|--|-----------|
| Tributyl phosphate | 126-73-8 | TWA (Inhalable fraction and vapor) | 5 mg/m ³ | ACGIH |
| | | TWA | 0.2 ppm 2.5 mg/m ³ | NIOSH REL |
| | | TWA | 5 mg/m ³ | OSHA Z-1 |
| | | TWA | 0.2 ppm 2.5 mg/m ³ | OSHA P0 |
| Dibutylphenylphosphate | 2528-36-1 | TWA | 0.3 ppm | ACGIH |
| butylated hydroxytoluene | 128-37-0 | TWA (Inhalable fraction and vapor) | 2 mg/m ³ | ACGIH |
| | | TWA | 10 mg/m ³ | NIOSH REL |
| | | TWA | 10 mg/m ³ | OSHA P0 |

Engineering measures : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 15000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

- Respiratory protection : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable.
If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
- Hand protection
- Remarks : Wear suitable gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations.
- Eye protection : Wear safety glasses with side shields (or goggles).
- Skin and body protection : Wear suitable protective clothing.
- Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : oily
- Color : purple
- Odor : odorless
- Odor Threshold : not determined
- pH : No data available
- Melting point/range : < -80 °F / < -62 °C

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 150000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

| | | |
|--|---|--|
| Boiling point/boiling range | : | not determined |
| Flash point | : | 345 °F / 174 °C |
| | | Method: Cleveland open cup |
| Evaporation rate | : | not determined |
| Upper explosion limit / Upper flammability limit | : | not determined |
| Lower explosion limit / Lower flammability limit | : | not determined |
| Vapor pressure | : | 0.27 hPa (77 °F / 25 °C) |
| Relative vapor density | : | not determined |
| Relative density | : | 1.0111 (77 °F / 25 °C) |
| Partition coefficient: n-octanol/water | : | No data available |
| Autoignition temperature | : | 876 °F / 469 °C |
| | | Method: ASTM D2155 |
| Decomposition temperature | : | not determined |
| Viscosity | | |
| Viscosity, dynamic | : | not determined |
| Viscosity, kinematic | : | < 2,000 mm ² /s (-65 °F / -54 °C) |
| | | 11.15 mm ² /s (100 °F / 38 °C) |
| | | 3.83 mm ² /s (210 °F / 99 °C) |
| Explosive properties | : | No data available |
| Oxidizing properties | : | No data available |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|---------------------------------|
| Reactivity | : | None reasonably foreseeable. |
| Chemical stability | : | Stable under normal conditions. |
| Possibility of hazardous reactions | : | None known. |
| Conditions to avoid | : | None known. |

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 150000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Emits acrid smoke and fumes when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute oral toxicity : LD50 (Rat, male and female): 2,100 mg/kg

Acute inhalation toxicity : LC50 (Rat, male): > 5.8 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: (highest concentration tested)

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 3,160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Components:**Tributyl phosphate:**

Acute oral toxicity : LD50 Oral (Rat, male and female): 1,553 mg/kg
Assessment: Harmful if swallowed.

LD50 Oral (Rat, male and female): 1,400 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 4.242 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 3,100 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Dibutylphenylphosphate:

Acute oral toxicity : Acute toxicity estimate (Rat, male and female): 2,400 - 3,000 mg/kg
Assessment: Not classified

Acute inhalation toxicity : LCLo (Rat, male and female): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 15000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

LC50 (Rat, male and female): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 5,000 mg/kg
Assessment: Not classified

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Acute oral toxicity : LD50 Oral (Rat, male and female): 4,470 mg/kg
Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 7,940 mg/kg

butylated hydroxytoluene:

Acute oral toxicity : LD50 Oral (Rat): > 6,000 mg/kg
Acute dermal toxicity : LD50 Dermal (Guinea pig): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Species : Rabbit
Exposure time : 24 h
Assessment : irritating
Result : moderate irritation

Components:**Tributyl phosphate:**

Species : Rabbit
Exposure time : 4 h
Assessment : Causes skin irritation.
Result : irritating

Dibutylphenylphosphate:

Species : Rabbit
Assessment : Not classified

Species : Humans
Exposure time : 24 h
Assessment : Not classified

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Species : Rabbit
Exposure time : 24 h
Assessment : Not classified as hazardous.
Result : slight to moderate irritation

Skydrol®LD4 Fire Resistant Hydraulic Fluid

Version Revision Date: SDS Number: Date of last issue: 08/06/2020
1.5 01/05/2023 150000093409 Date of first issue: 09/06/2016
PRD SDSUS / Z8 / 0001

Components:**Tributyl phosphate:**

Test Type : Skin Sensitization
Species : Guinea pig
Assessment : Not classified
Result : Does not cause skin sensitization.

Test Type : Skin Sensitization
Species : Humans
Assessment : Not classified
Result : Does not cause skin sensitization.

Dibutylphenylphosphate:

Test Type : Human experience
Species : Humans
Assessment : Not classified
Result : non-sensitizing

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Test Type : Skin Sensitization
Species : Guinea pig
Result : May cause sensitization by skin contact.

butylated hydroxytoluene:

Test Type : Skin sensitization
Species : Guinea pig
Result : non-sensitizing

Germ cell mutagenicity

Not classified based on available information.

Product:

Genotoxicity in vitro : Test Type: Salmonella typhimurium assay (Ames test)
Metabolic activation: +/- activation
Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Chromosome Aberration Test
Result: negative

Components:**Tributyl phosphate:**

Genotoxicity in vitro : Test Type: Mutagenicity - Bacterial
Metabolic activation: +/- activation
Method: Bacterial Reverse Mutation Assay
Result: negative

Skydrol®LD4 Fire Resistant Hydraulic Fluid

Version 1.5 PRD Revision Date: 01/05/2023 SDS Number: 15000093409 Date of last issue: 08/06/2020
Date of first issue: 09/06/2016
SDSUS / Z8 / 0001

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Chromosome Aberration Test
Result: equivocal

Genotoxicity in vivo : Species: Rat (male and female)
Application Route: oral: gavage
Method: Mammalian Bone Marrow Chromosome Aberration Test
Result: negative

Dibutylphenylphosphate :

Genotoxicity in vitro : Test Type: Salmonella typhimurium assay (Ames test)
Metabolic activation: +/- activation
Method: Bacterial Reverse Mutation Assay
Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Cell Gene Mutation Test
Result: negative

Test Type: Chromosome aberration test in vitro
Metabolic activation: +/- activation
Method: In vitro Mammalian Chromosome Aberration Test
Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: - activation
Method: OECD Guideline 482
Result: negative

Genotoxicity in vivo : Species: Rat (male and female)
Application Route: intraperitoneal injection
Result: negative

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Genotoxicity in vitro : Test Type: Salmonella typhimurium assay (Ames test)
Metabolic activation: +/- activation
Method: Bacterial Reverse Mutation Assay
Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Chromosome Aberration Test
Result: equivocal

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Cell Gene Mutation Test
Result: negative

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 150000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

STOT-repeated exposure

Not classified based on available information.

Product:

Remarks : No data available

Components:**Tributyl phosphate:**

Assessment : Based on available data, the classification criteria are not met.

Dibutylphenylphosphate:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Respiratory system
Assessment : Not classified

Repeated dose toxicity**Product:**

Species : Rat, male and female
NOAEL : 40 mg/m³
Application Route : Inhalation
Exposure time : 28 days
Target Organs : Blood, Respiratory system
Remarks : Irritating to eyes and respiratory system.

Components:**Tributyl phosphate:**

Species : Mouse, male and female
: 75 mg/kg
Application Route : in feed
Exposure time : 90 days

Dibutylphenylphosphate:

Species : Rat, male and female
NOAEL : 5 mg/kg
LOAEL : 50 mg/kg
Application Route : oral (feed)
Exposure time : 90 days

Species : Rat, male and female
: 5 mg/m³
Application Route : Inhalation
Exposure time : 90 days

Species : Rabbit, male and female
NOAEL : 100 mg/kg bw/day
Application Route : Dermal Study
Exposure time : 21 d

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 150000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

Aspiration toxicity

Not classified based on available information.

Product:

Not applicable

Components:**7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:**

Not applicable

Experience with human exposure**Product:**

| | | |
|--------------|---|---|
| Inhalation | : | Remarks: None known. |
| Skin contact | : | Remarks: Causes skin irritation. |
| Eye contact | : | Remarks: Contact with the eyes may be very painful but does not cause damage. |
| Ingestion | : | Remarks: None known. |

Further information**Product:**

Remarks : None known.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

| | | |
|---|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 5.2 mg/l Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | LC50 (Daphnia magna (Water flea)): 5.8 mg/l Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | EC50 (Selenastrum capricornutum (green algae)): 8.2 mg/l Exposure time: 96 h |

Components:**Tributyl phosphate:**

| | | |
|---|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 1.8 mg/l Exposure time: 48 h |

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 150000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 1.1 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.82 mg/l
Exposure time: 95 d

1.7 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.3 mg/l
Exposure time: 21 d

Dibutylphenylphosphate:

Toxicity to fish : LL50 (Cyprinus carpio (Carp)): 1.8 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.4 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): 9.6 mg/l
Exposure time: 72 h
Method: EL50 method of the water accommodated fraction (W.A.F.)

NOELR (Selenastrum capricornutum (green algae)): 3.5 mg/l
Exposure time: 72 h
Method: EL50 method of the water accommodated fraction (W.A.F.)

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 0.11 mg/l
Exposure time: 60 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.106 mg/l
Exposure time: 21 d

butylated hydroxytoluene:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.57 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.48 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 0.24 mg/l
Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (algae)): 0.24 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oryzias latipes (Orange-red killifish)): 0.053 mg/l
Exposure time: 30 d

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 150000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

Bioconcentration factor (BCF): 35
Method: OECD Test Guideline 305

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : This product meets the criteria for a synthetic used oil under the U.S. EPA Standards for the Management of Used Oil (40 CFR 279). Those standards govern recycling and disposal in lieu of 40 CFR 260 -272 of the Federal hazardous waste program in states that have adopted these used oil regulations. Consult your attorney or appropriate regulatory official to be sure these standards have been adopted in your state. Recycle or burn in accordance with the applicable standards.
Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 150000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Carcinogenicity
Skin corrosion or irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : On the inventory, or in compliance with the inventory

AIIC : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to a Significant New Use Rule:
Potassium decafluoro- 67584-42-3
ro(pentafluoroethyl)cyclohexanesulphonate


No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION**Further information**

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Version
1.5
PRDRevision Date:
01/05/2023SDS Number:
150000093409
SDSUS / Z8 / 0001Date of last issue: 08/06/2020
Date of first issue: 09/06/2016

NFPA 704:



HMIS® IV:

| | | |
|-----------------|---|---|
| HEALTH | * | 2 |
| FLAMMABILITY | | 1 |
| PHYSICAL HAZARD | | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

| | | |
|-----------------|---|---|
| ACGIH | : | USA. ACGIH Threshold Limit Values (TLV) |
| NIOSH REL | : | USA. NIOSH Recommended Exposure Limits |
| OSHA P0 | : | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values) |
| OSHA Z-1 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| NIOSH REL / TWA | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| OSHA P0 / TWA | : | 8-hour time weighted average |
| OSHA Z-1 / TWA | : | 8-hour time weighted average |

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable

Skydrol®LD4 Fire Resistant Hydraulic Fluid

| | | | |
|---------|----------------|-------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 08/06/2020 |
| 1.5 | 01/05/2023 | 150000093409 | Date of first issue: 09/06/2016 |
| PRD | | SDSUS / Z8 / 0001 | |

Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to : www.EastmanAviationSolutions.com
compile the Material Safety
Data Sheet

Revision Date : 01/05/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8