



Long Life Reliability
does not cost the earth

**Connection
Systems**

MODEL TWIN RBL4000 LITHIUM

Power unit for aircraft and combat vehicles

www.lpa-group.com

www.redboxaviation.com

- Totally weather protected
- Maintenance free
- Tough and compact
- No memory effect
- Works in any orientation
- High charge retention
- Long shelf life
- Fast recharge
- No cycling
- Leak proof
- Cells replaceable on condition
- Heavy duty engine starting of turbo prop, turbine, aircraft and helicopters
- Lightweight portable start power at remote locations
- External charger for prolonged unit life



SUPPLIED WITH UNIT

2x charger

Output cable

Parallel joining cable

2 x thermal protection bag

OPTIONAL EXTRAS

Twin trolley

Various output cable lengths

Croc clips

Various connectors

Carry case available

TWIN RBL4000 SPECIFICATION

Max amps	3000 (nom. short circuit current) 8000 (max. short circuit current)
Capacity	56 amps hrs @ 10 hr rate
Max voltage	28VDC
Size (mm)	L 350 x W 200 x H 380
Weight (KG)	30
Operating temperature	-40°C to +55°C
Case	Aluminium
Voltage indication	Digital to IP65
Auxiliary protection	Circuit breaker 40A
Output cable	2m heavy duty cable with aircraft connector
Charger	2 x 4 amp electronic universal AC input



enquiries@lpa-connect.com
+44(0) 1799 512800
www.lpa-group.com
www.redboxaviation.com

Light & Power House
Shire Hill
Saffron Walden, Essex
CB11 3AQ, UK

Specification may change without notice

REV-11-24-2