



LITHIUM ION RECHARGEABLE BATTERY PACK UN IATA 38.3 CERTIFICATE

Manufacturer:

National Power Corporation
4330 W. Belmont Ave.
Chicago, IL. 60641
Telephone: +773-685-2662 Fax: +773-685-8316

Product:

Lithium-Ion Rechargeable Battery Pack Specification

MODEL: SM201 (2SA07A95)		
Item	Value	Comments
Nominal Voltage	11.1	
Battery Pack (mAh)	4200	
Battery Pack (Wh)	47	
Configuration	3S-2P	
Product Category	N/A	Lithium – Ion Rechargeable Battery Pack
Chemical System	N/A	Lithium – Ion
Appearance	N/A	Battery Pack in plastic enclosure

IATA T1 – T8 CERTIFICATE

BATTERY PACK TEST FILE NUMBER: U-050905

Test and Criteria (UN38.3 LITHIUM – ION BATTERY)			
No.	Test Procedure	Test Results	Comments
T1	Altitude Stimulation	Pass	
T2	Thermal Test	Pass	
T3	Vibration	Pass	
T4	Shock	Pass	
T5	External Short Circuit	Pass	
T6	Impact		For Cell Only
T7	Overcharge	Pass	
T8	Forced Discharge		For Cell Only

According to the requirements of UN/DOT 38.3, lithium cells and batteries are subject to as many as eight separate tests designed to assess their ability to withstand the anticipated rigors incurred during transport.

We, National Power Corporation, certify the model listed in this document complies with T1 to T8 test as required.

National Power Corporation
Engineering Department

Mauricio Medina 6/27/17

Mauricio Medina, Engineering Manager
National Power Corporation
改善 Kaizen - It's the Way We Work

05/09/2005
Report Date

Lithium Battery Safety Document

Required: For any shipment where the lithium ion battery handling label is required (sections IB or II)



Warning: Lithium batteries that have been recalled by the manufacturer for safety reasons must not be shipped by air.

Terminology:

Cell - electrochemical unit, consisting of an anode and a cathode, capable of generating electrical current

Battery - assembly of cells

Lithium ion cells/batteries -rechargeable-includes lithium polymer cells/batteries

This package contains lithium cell or batteries in the following configuration (check applicable):

<input type="checkbox"/>	Lithium Ion-Maximum of 20 Watt hours per cell: and 100 Watt hours per battery
<input type="checkbox"/>	CELLS OR BATTERIES ONLY (ICAO/IATA Packing Instruction 965, Section II) Cells or batteries in a package without electronic equipment Package Limit: ≤ 2.7 Wh = 2.5 kg: or > 2.7 Wh but ≤ 20 Wh = 8 cells: or > 2.7 Wh but ≤ 100 Wh = 2 batteries
<input checked="" type="checkbox"/>	CELLS OR BATTERIES ONLY (ICAO/IATA Packing Instruction 965, Section IB) Cells or batteries in a package, without electronic equipment

This package must be handled with care. A flammability hazard exists if the package is damaged.

If this package is damaged in transportation, it must not be loaded until the condition of the contents can be verified. The batteries contained in this package must be inspected for damage and may only be repacked if they are intact and protected against short circuits.

For more information about the batteries contained in this package, call the following telephone number (Chemtrec CCN232907):

1-800-424-9300 North America

1-703-527-3887 International



Product Name: Lithium Ion Battery
 NPC Document: SDS-10 Rev 2018
 Effective Date: January 1, 2018

Safety Data Sheet for Chemical Products (SDS)

1. PRODUCT AND COMPANY IDENTIFICATION

- Product name: Lithium ion rechargeable battery
- Product code: None
(Models assembled with individual cell capacities of less than or equal to 5.4Ah)
- Company name: National Power Corporation
- Address: 4330 W. Belmont Ave., Chicago, IL. 60641, USA
- Telephone number: +773-685-2662
- Fax number: +1-773-685-8316
- Emergency telephone number: [North America] 1-800-424-9300 [International] 001-703-527-3887

2. HAZARDS IDENTIFICATION

For the battery cell, chemical materials are stored in a hermetically sealed metal or metal laminated plastic case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials' leakage.

However, if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery cell case will be breached at the extreme, hazardous materials may be released.

Moreover, if heated strongly by the surrounding fire, acrid gas may be emitted.

- GHS classification: Not available
(This product is outside the scope of GHS system since it's considered as an "article".)
- Most important hazard and effects
 Human health effects:
 Inhalation: The steam of the electrolyte has an anesthesia action and stimulates a respiratory tract.
 Skin contact: The steam of the electrolyte stimulates a skin. The electrolyte skin contact causes a sore and stimulation on the skin.
 Eye contact: The steam of the electrolyte stimulates eyes. The electrolyte eye contact causes a sore and stimulation on the eye. Especially, substance that causes a strong inflammation of the eyes is contained.
 Environmental effects: Since a battery cell remains in the environment, do not throw out it into the environment.
- Specific hazards:
 If the electrolyte contacts with water, it will generate detrimental hydrogen fluoride.
 Since the leaked electrolyte is inflammable liquid, do not bring close to fire.

3. COMPOSITION / INFORMATION ON INGREDIENTS

- Substance or preparation: Preparation
- Information about the chemical nature of product: *1

Portion	Material name	Concentration range (wt %)
Positive electrode	Lithium transition metal oxidate ($\text{Li}[\text{M}]_m[\text{O}]_n$ *2)	20~60
Positive electrode's base	Aluminum	1~10
Negative electrode	Carbon	10~30
Negative electrode's base	Copper	1~15
Electrolyte	Organic electrolyte principally involves ester carbonate	5~25
Outer case	Aluminum, iron, aluminum laminated plastic	1~30



Product Name: Lithium Ion Battery
NPC Document: SDS-10 Rev 2018
Effective Date: January 1, 2018

Safety Data Sheet for Chemical Products (SDS)

**1 Not every product includes all of these materials.*

**2 The letter M means transition metal and candidates of M are Co, Mn, Ni and Al. One compound includes one or more of these metals and one product includes one or more of the compounds. The letter m and n means the number of atoms.*

4. FIRST-AID MEASURES

Spilled internal cell materials

- Inhalation:
Make the victim blow his/her nose, gargle. Seek medical attention if necessary.
- Skin contact:
Remove contaminated clothes and shoes immediately. Wash extraneous matter or contact region with soap and plenty of water immediately.
- Eye contact:
Do not rub one's eyes. Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention immediately.

A battery cell and spilled internal cell materials

- Ingestion:
Make the victim vomit. When it is impossible or the feeling is not well after vomiting, seek medical attention.

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media: Plenty of water, carbon dioxide gas, nitrogen gas, chemical powder fire extinguishing medium and fire foam.
- Specific hazards: Corrosive gas may be emitted during fire.
- Specific methods of fire-fighting: When the battery burns with other combustibles simultaneously, take fire-extinguishing method which correspond to the combustibles. Extinguish a fire from the windward as much as possible.
- Special protective equipment for firefighters:
 - Respiratory protection: Respiratory equipment of a gas cylinder style or protection-against-dust mask
 - Hand protection: Protective gloves
 - Eye protection: Goggle or protective glasses designed to protect against liquid splashes
 - Skin and body protection: Protective cloth

6. ACCIDENTAL RELEASE MEASURES

Spilled internal cell materials, such as electrolyte leaked from a battery cell, are carefully dealt with according to the followings.

- Precautions for human body:
Remove spilled materials with protective equipment (protective glasses and protective gloves). Do not inhale the gas as much as possible. Moreover, avoid touching with as much as possible.
- Environmental precautions: Do not throw out into the environment.
- Method of cleaning up: The spilled solids are put into a container. The leaked place is wiped off with dry cloth.
- Prevention of secondary hazards: Avoid re-scattering. Do not bring the collected materials close to fire.



Product Name: Lithium Ion Battery
 NPC Document: SDS-10 Rev 2018
 Effective Date: January 1, 2018

Safety Data Sheet for Chemical Products (SDS)

7. HANDLING AND STORAGE

• Handling suggestions

- Do not connect the positive terminal to the negative terminal with electrical wire or chain.
- Avoid polarity reverse connection when installing the battery to an instrument.
- Do not wet the battery with water, seawater, drink or acid; or expose to strong oxidizer.
- Do not damage or remove the external tube.
- Keep the battery away from heat and fire.
- Do not disassemble or reconstruct the battery; or solder the battery directly.
- Do not give a mechanical shock or deform.
- Do not use unauthorized charger or other charging method. Terminate charging when the charging process doesn't end within specified time.

• Storage

- Do not store the battery with metalware, water, seawater, strong acid or strong oxidizer.
- Make the charge amount 30~50% then store at room temperature or less (temperature= -20~35 degree C) in a dry (humidity: 45~85%) place. Avoid direct sunlight, high temperature, and high humidity.
- Use insulative and adequately strong packaging material to prevent short circuit between positive and negative terminal when the packaging breaks during normal handling. Do not use conductive or easy to break packaging material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION (WHEN THE ELECTROLYTE LEAKS)

• Control parameters

ACGIH has not been mentioned control parameter of electrolyte.

• Personal protective equipment

Respiratory protection: Respirator with air cylinder, dust mask

Hand protection: Protective gloves

Eye protection: Goggles or protective glasses designed to protect against liquid splashes

Skin and body protection: Working clothes with long sleeve and long trousers

9. PHYSICAL AND CHEMICAL PROPERTIES

• Appearance

Physical state: Solid

Form: Cylindrical or Prismatic or Pouch (laminated)

Color: Metallic color or black (without tube if it has

tube) Odor: No odor

10. STABILITY AND REACTIVITY

• Stability: Stable under normal use

• Hazardous reactions occurring under specific conditions

- Conditions to avoid: When a battery cell is exposed to an external short-circuit, crushes, deformation, high temperature above 100 degree C, it will be the cause of heat generation and ignition. Direct sunlight and high humidity.
- Materials to avoid: Conductive materials, water, seawater, strong oxidizers and strong acids.
- Hazardous decomposition products: Acrid or harmful gas is emitted during fire.



Product Name: Lithium Ion Battery
 NPC Document: SDS-10 Rev 2018
 Effective Date: January 1, 2018

Safety Data Sheet for Chemical Products (SDS)

11. TOXICOLOGICAL INFORMATION

Organic Electrolyte

- Acute toxicity:
LD₅₀, oral - Rat 2,000mg/kg or more
- Irritating nature: Irritative to skin and eye

12. ECOLOGICAL INFORMATION

- Persistence/degradability:
Since a battery cell and the internal materials remain in the environment, do not bury or throw out into the environment.

13. DISPOSAL CONSIDERATIONS

- Recommended methods for safe and environmentally preferred disposal:

Product (waste from residues)

Specified collection or disposal of lithium ion battery is required by the law like as "battery control law" in several nations. Collection or recycle of the battery is mainly imposed on battery's manufacturer or importer in the nations recycle is required.

Contaminated packaging

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery cell contaminates, dispose as industrial wastes subject to special control.

14. TRANSPORT INFORMATION

In the case of transportation, avoid exposure to high temperature and prevent the formation of any condensation. Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo piles and wet by rain. The container must be handled carefully. Do not give shocks that result in a mark of hitting on a cell. Please refer to Section 7-HANDLING AND STORAGE also.

UN regulation

- UN number: 3480 (3481 when the battery is contained in equipment or packed with equipment)
- Proper shipping name:
Lithium ion batteries ("lithium ion batteries contained in equipment" or "lithium ion batteries packed with equipment")
- Class: 9 *
- Packing instruction: 965 (966 or 967 when battery is packaged with equipment or contained in equipment).

** Although this product meets the criteria of "dangerous goods" and are classified as "lithium ion batteries", depending on the battery's total capacity in the packaging, etc., they may not be subject to the fully regulated provisions.*

Regulation depends on region and transportation mode

- Worldwide - Air transportation:
ICAO/IATA-DGR [packing instruction 965 sections IB or II]
(When shipping batteries "packed with" or "contained in" equipment, use packing instruction 966 or 967 as appropriate.)
- Worldwide - Ocean transportation:
IMO-IMDG Code [special provision 188]
- Europe - Ground transportation:
ADR [special provision 188]

** Instructions or provisions in the box brackets are conditions to make the battery cell exempted from full regulation.*



Product Name: Lithium Ion Battery
NPC Document: SDS-10 Rev 2018
Effective Date: January 1, 2018

Safety Data Sheet for Chemical Products (SDS)

15. REGULATORY INFORMATION

- Regulations specifically applicable to the product:
Wastes Disposal and Public Cleaning Law [Japan]
Law for Promotion of Effective Utilization of resources [Japan]
US Department of Transportation 49 Code of Federal Regulations [USA]

** About overlapping regulations, please refer to Section 14-TRANSPORT INFORMATION.*

16. OTHER INFORMATION

- This safety data sheet is offered an agency who handles this product to handle it safely.
- The agency should utilize this safety data sheet effectively (put it up, educate person in charge) and take proper measures.
- ***The information contained in this Safety data sheet is based on the present state of knowledge and current legislation.***
- This safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Reference

Dangerous Goods Regulations – 59th Edition Effective 1 January 2018: International Air Transport Association (IATA)
IMDG Code – 2016 Edition: International Maritime Organization (IMO)
The European Agreement concerning the International Carriage of Dangerous Goods by Road – 2017:
The United Nations Economic Commission for Europe (UNECE)

Reference

Reference Document: SDS-IBT-00026-21_E, 2018